

DIRECT CONNECT TO LYNX FAMILY PANELS WITH CIA MODEM

MATERIALS NEEDED

- ADEMCO CIA MODEM
- WATELCO CABLE (COMES WITH MODEM)
- 12V BATTERY W/CONNECTING WIRE

CONNECTIONS

1. Plug in power on the modem and connect it to the computer using a serial cable to the computers COM port. (an *approved* USB to Serial adapter will work)
2. Connect the WATELCO cable into the LINE jack on the back of the CIA Modem.
3. Connect the Green wire to terminal 2 of the Lynx panel.
4. Connect the Red wire to terminal 3 of the Lynx panel.
5. Connect the Black wire to terminal 7 of the Lynx Panel
6. Connect the Yellow wire to the Positive terminal of the 12V Battery.
7. Connect a wire from terminal 7 to the Negative terminal of the 12V Battery.

PROCEDURE

1. Start Compass on your computer, open your Lynx account, and click **Communications** from the menu bar.
2. Locate and click **Connect**.
3. Using the drop down list, select "Initiate from" **Telco**.
4. Click on **Connect** to setup the modem.
5. Using the Lynx panel's keypad, enter your **Installer Code + # + 1** ("starts" the panel).
6. Now click **OK**, to acknowledge that the panel has been started.
7. You should hear modem tones and see the panel begin to make its connection to Compass.

