

# VISTA-15



*The flexibility you want with the end-user features and security enhancements your customers need.*

False alarm reducing features, security enhancements and end user appeal make the economical **Vista-15** the industry's most sophisticated, versatile control.

With both hardwire and wireless expansion and features like *Night Arming* and *Cancel Verification*, the Vista-15 can meet even the most demanding requirements.

### Superior Flexibility

Vista-15 has the installation flexibility & expandability to be used in simple configurations, complex installs and everything in between.

- ◆ Six Hardwired Zones
- ◆ Expands to 32 Total Zones (up to 26 wireless and/or 14 hardwired zones)
- ◆ 16 User Codes
- ◆ 48 Event Log with Date/Time Stamp
- ◆ Two-Wire or Four-Wire Smoke Detectors
- ◆ Fast and easy E2 programming mode

### Security & False Alarm Reducing Enhancements

Vista-15 has incorporated SIA false alarm reducing requirements with the latest technology.

- ◆ Exit Delay Reset
- ◆ Alarm Cancel Verification
- ◆ Unvacated "Auto-Stay"
- ◆ Cross Zoning/Alarm Verification
- ◆ Short vs. Open Detection & Reporting
- ◆ Telephone-Line Monitor
- ◆ Arming Level Increase

### Valuable End User System Features

Vista-15 offers your customers a choice of system features that add value to any install.

- ◆ Easy-to-Use Single Button Operation
  - Arm Away
  - Arm Stay
  - Arm Night
  - Page
- ◆ Quick Exit
- ◆ Quick Arm
- ◆ X-10 Control & 4 Relays Supported for Home Management
- ◆ Enhanced Paging Capabilities
- ◆ 24-Hour Monitoring Zone
- ◆ Compatible Keypad Family

## VISTA-15

### Wide Selection of Easy to Use End User Interface Devices

With superior wireless remote control, phone operation and choice of keypads, Vista-15 can be easily operated to fit your customers needs.

- ◆ Wireless remote control
  - **5804** - Four button, fully programmable key
  - **5804BD** - Four button, fully programmable key with status feedback for added security
  - **5827BD** - Wireless keypad with status feedback
- ◆ Phone Control
  - **4285** - Turns any touch-tone phone into a voice response keypad

### SPECIFICATIONS:

#### ELECTRICAL

- ◆ Aux power 12 VDC, 600mA max
- ◆ Seven hour standby at 400 mA aux load with 4 amp hour battery
- ◆ 16.5 VAC/25 VA transformer
- ◆ Alarm output 12 VDC, 2.0 amps max
- ◆ For UL installations, combined aux and alarm output cannot exceed 700mA

#### OUTPUT CONTROL

- ◆ Supports one relay board (part no. 4204) for control of up to four relays
- ◆ Optional X-10 transformer/interface (part no. 4300) may be used to control up to four X-10 receiving devices

#### ZONES

- ◆ Six hardwired zones
- ◆ Selectable response: 10msec, 350msec, 750msec
- ◆ 16 zone types to choose from
- ◆ Programmable swinger suppression

### SUPPORTED DEVICES

#### Hardwired Expansion Devices

- ◆ 4219 - eight hardwired zones - 16mA
- ◆ 4204 up to four relays - 15mA standby (each active relay draws an additional 40mA)
- ◆ 4229 - eight hardwired zones and two relays - 36mA
- ◆ Powerline Support
  - 4300 transformer/interface
- ◆ Keypads
  - 6128 fixed English LCD - 85mA/40mA
  - 6139 custom English (required for programming) - 100mA
- ◆ Voice module 4285 VIP - 160mA
- ◆ Supports 16 two-wire smoke detectors
- ◆ 5881L up to 8 zones - 50mA, 5881M up to 16 zones - 50mA, 5881H up to 26 zones - 50mA
- ◆ Supports Eagle 1225 & 1221 boards

#### AGENCY LISTINGS

- ◆ UL Residential Fire and Burglary and CFM

#### Communications

- ◆ Touch tone or pulse
- ◆ Formats supported
  - ADEMCO contact ID
  - ADEMCO 4 + 2 Express
  - ADEMCO low speed
  - Sescoa/Radionics
- ◆ 3 + 1, 4 + 1 and 4 + 2 reporting
- ◆ Reporting capabilities
  - Split
  - Dual
  - Split/Dual - True dial tone detection
- ◆ Low battery reports 11.2 - 11.6 VDC
- ◆ AC loss and restoral reporting supported

#### Ordering Information

Part No.	Description
Vista - 15	Control Panel