

## ADEMCO VISTA-15P

### Control Panel



The versatile Vista-15P is the ideal choice for any residential installation. Hardwired expansion, two-wire smoke detectors, scheduling options and a host of end-user and installer features separate the ADEMCO VISTA-15P from all other six-zone panels – offering you and your customers the most panel for the dollar.

### FEATURES

- Six on-board hardwired zones —
  - 16 hardwired expansion zones totalling 22
  - 26 wireless expansion zones
- Eight independent keyfob zones allow wireless keys to be programmed without using any of the 26 zones
- Eight output devices
  - Relays (Model 4204 Relay Modules, or 4229 Expansion Module), and/or
  - X-10® devices (when used with a 4300 Transformer)
- Two low current on-board trigger outputs
- 50 Event Log viewable at system keypads with time/date stamp
- 32 system user codes
- Two installer configurable zone types allows the installer to "create custom zone types" by assigning all zone attributes
- Multiple actions on output devices depending on system "state"
  - Turns light off when system arms
  - Turns same lights on when system disarms
  - Flashes same lights when system is in alarm

- Built-in phone line cut monitor with programmable delay and annunciation options
  - Display on system keypads
  - Trigger local sounders
  - Trigger system bell
- Supports four-wire, and up to 16 two-wire smokes
  - Works with Sentrol CleanMe™ maintenance signal

#### Valuable End-User Features

- Now viewable on system keypads:
  - Exit countdown
  - Time and date display\*
  - Event log\*
- Auto keypad backlighting on entry
- Keyswitch arming
- Programmable macro buttons and single-button arming
- A variety of wireless remote controls for single-button operation
- User Scheduling
  - Automatically activates X-10 and relays at programmed times
  - Latchkey reports to pagers
  - Auto arm/disarm
  - "User access" time windows

- Supports up to two numeric pagers
- VIP Module allows system control from any touchtone phone
- Chime by zone

#### Security Dealer Features

- Programmable to meet SIA false alarm prevention specifications. To meet UL approval for ANSI/SIA CP-01-2000 order part number VISTA-20PSIA
- Automatic System Load Shed
  - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure. Reduces service calls to replace batteries
- Dynamic Signaling
  - Reduces redundant reporting to the central station when multiple reporting methods are used; i.e. digital dialer and AlarmNet Radio

\*Requires custom alpha keypad

# ADEMCO VISTA-15P

## Control Panel

### SPECIFICATIONS

#### Electrical

- Aux. power 12VDC, 600mA maximum
- Seven hour standby at 400mA aux. load with four amp hour battery
- 16.5VAC/25VA transformer
- Alarm output 12VDC, 2.0 amps maximum
- For UL installations, combined aux. and alarm output cannot exceed 700mA

#### Output Control

- Supports a maximum of eight output devices (combination of relays and/or X-10) plus two onboard triggers

#### Zones

- Six hardwired zones
- Selectable response: 10msec, 350msec, 750msec
- 16 selectable zone types plus two configurable zone types
- Programmable swinger suppression

#### Expansion Devices

- 4219 – Eight hardwired zones – 16mA

- 4204 – Up to four relays – 15mA standby (each active relay draws an additional 40mA)
- 4229 – Eight hardwired zones and two relays – 36mA (each active relay draws an additional 40mA)

#### Accessories

- 4286 VIP Voice Module – 220mA
- 5881ENL supports up to eight zones – 60mA, 5881ENM supports up to 16 zones – 50mA, 5881ENH supports up to 26 zones – 50mA
- 5883 Transceiver supports up to 26 zones – 80mA
- Supports Eagle 1225 and 1221 boards

#### Keypads

- 6160 Custom Alpha (required for programming) – 100mA
- 6160V Custom Alpha Voice – 100mA
- 6150 Fixed English LCD - 85mA/40mA
- 6150V Fixed English Voice LCD – 85mA/40mA
- 6150RF Fixed English RF LCD - 85mA/40mA
- 6148 Fixed English LCD – 70mA/30mA

#### Agency Listings

- UL Residential Fire, Burglary and CSFM

#### Smoke Detectors

- Supports up to 16 two-wire smoke detectors
- Supports four-wire smoke detectors

#### Communications

- Touchtone or pulse
- Formats supported
  - ADEMCO Contact ID
  - ADEMCO 4 + 2 Express
  - ADEMCO low speed
  - Sescoa/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
  - Split
  - Dual
  - Split/Dual – True dial tone detection
- Low battery reports 11.2 – 11.6VDC
- AC loss and restoral reporting supported

### ORDERING

<b>VISTA-15P</b>	Control Panel
<b>VISPACK</b>	Preboxed Kit

#### Honeywell Security & Custom Electronics

165 Eileen Way, Syosset, NY 11791  
www.ademco.com