



UL INSTALLATIONS
 THE MINIMUM WIRE SIZE USED FOR TELEPHONE INSTALLATIONS MUST BE #26 GAUGE

WARNING:
 TO PREVENT RISK OF SHOCK DISCONNECT TELEPHONE LINE AT TELECOM JACK BEFORE SERVICING THIS UNIT.

UL NOTE
 THE MINIMUM WIRE SIZE USED FOR TELEPHONE INSTALLATIONS MUST BE #26 GAUGE

UL INSTALLATIONS
 THE MINIMUM WIRE SIZE USED FOR TELEPHONE INSTALLATIONS MUST BE #26 GAUGE

EXTERNAL SOUNDERS AND POWERLINE CARRIER DEVICES HAVE NOT BEEN EVALUATED BY UL.

FCC ID: CFS8DLVXNREN-6
 (LYNXR-I) COMPLIES WITH
 FCC RULES, PART 68 FCC
 REGISTRATION
 No. 5GBUSA-25623-AL-E
 RINGER EQUIVALENCE: 0.6B

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

UL NOTE
 THE MINIMUM WIRE SIZE USED FOR TELEPHONE INSTALLATIONS MUST BE #26 GAUGE

UL NOTE
 THE MINIMUM WIRE SIZE USED FOR TELEPHONE INSTALLATIONS MUST BE #26 GAUGE

UL NOTE
 THE MINIMUM WIRE SIZE USED FOR TELEPHONE INSTALLATIONS MUST BE #26 GAUGE

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

NOTE
 USE ONLY THE K10145X10 OR K10145CN CLASS 2 TRANSFORMERS PROVIDED

POWER SHUTDOWN NOTE: AT 6.0VDC THE SYSTEM WILL NOT OPERATE.

THE LYNXR-I CONTROL IS COMPATIBLE WITH THE FOLLOWING INTEGRAL RECHARGEABLE BATTERY PACKS:
 P/N LYNXRCHKIT-SC
 P/N LYNXRCHKIT-TC
 P/N LYNXRCHKIT-SHA
REPLACE EVERY FOUR YEARS

THIS EQUIPMENT SHOULD BE INSTALLED IN ACCORDANCE WITH THE NATIONAL FIRE PROTECTION ASSOCIATION STANDARDS ANS/NFPA 70 NATIONAL ELECTRIC CODE AND NFPA 72 NATIONAL FIRE ALARM CODE, CHAPTER 2 (NATIONAL FIRE PROTECTION ASSOC., BATTERYMARCH PARK, QUINCY, MA 02269), PRINTED INFORMATION DESCRIBING PROPER INSTALLATION, EVACUATION PLANNING AND REPAIR SERVICE IS TO BE PROVIDED WITH THIS EQUIPMENT.

LYNXR-I ALSO COMPLIES WITH THE FOLLOWING:
 CANADIAN STANDARDS ASSOCIATION (CSA) C22.1, CANADIAN ELECTRICAL CODE, PART 1, SAFETY STANDARD FOR ELECTRICAL INSTALLATIONS AND CAN/ULC-S540, INSTALLATION OF RESIDENTIAL FIRE WARNING SYSTEMS.

THIS DEVICE COMPLIES WITH PART 15 OF FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE OPERATION.

***WHEN AVAILABLE**

LYNXR-I SUMMARY OF CONNECTIONS