

DEALER SUCCES\$\$ BULLETIN



GENERATE INSTANT SAVINGS FOR YOUR CUSTOMERS WITH THE TL300 UNIVERSAL IP ALARM COMMUNICATOR

**Compatible with any control panel
that uses the Contact ID format***

A valuable addition to the award-winning T-Link family of Internet/network alarm communicators

The simple-to-install TL300 saves your customers money by taking advantage of their existing Internet connections and security equipment to create fully supervised security solutions between protected premises and central monitoring stations. This method provides flexibility and an always-on, two-way line of communication. The TL300 is ideal for commercial, retail, industrial and government complexes and multi-unit residential units.

- Connects directly to the telephone output of a control panel and simulates a telephone connection.
- Eliminates the need to maintain 2 phone lines for fire monitoring, helping to save customers money.
- No fear of line cuts; more reliable, supervised security (90 second intervals).
- UL AA High-Line Security, ULC Level 3/4/5 and CE listed.
- Eliminates security risks through industry-leading, 128-bit AES encryption (NIST approved).
- Capable of reporting to different e-mail addresses.
- Ships complete with PC5003C cabinet.

The TL300 is compatible with our PowerSeries™ and MAXSYS® control panels and reports to Sur-Gard System III virtual receivers.

*Control panels must follow the Contact ID specification of 40 ms/60 ms on/off time.

Contact your DSC distributor
www.dsc.com
1-888-888-7838

DSC®

tyco / Fire &
Security