



D625 Series VFD Keypads



- ▶ Two-line, 16-character bright-blue vacuum fluorescent display (VFD)
- ▶ Light emitting diode (LED) system status indicator
- ▶ 19 keys, including three programmable emergency keys
- ▶ Sounder that emits eight warning tones

Each D625 Series Keypad model is low-profile, surface-mountable, and compatible with D6412 and D4412 Control Panels. Each keypad model has an illuminated keypad, bright-blue vacuum fluorescent (VFD), three programmable emergency keys, and a sounder display that emits eight warning tones.

Functions

LED and VFD

Each D625 Series Keypad model has two LEDs: Status and On. The models also use words, numbers, and symbols to show the status of the security system on the vacuum fluorescent display (VFD). When several events occur, each model shows each event in order of priority.

Keys

Each D625 Series Keypad model has a total of 19 keys for specific functions. Use the 10 numeric keys, the [CMD] key, and the [*] key for entering passcodes, issuing commands, and choosing the next display. Use the [ALL ON], [PART ON], or [NO DELAY] keys to arm your system. Use the [BYPASS] key to bypass points. Your installing company can program the [A], [B], and [C] keys with functions such as Emergency, Fire, or Panic. When pressed, each key emits a muted beep.

Audible Tones

The sounder emits eight warning tones:

- Fire Alarm: Indicates a fire event. Evacuate occupants and investigate for smoke or fire.
- Burglary Alarm: Indicates a burglary event.
- Trouble: Indicates that a system component requires attention, such as a broken wire or a low battery.
- Exit Delay: Indicates that the system is on and you must exit the area within the time limit to avoid an alarm condition.
- Entry Delay: Indicates that the system is on and you must turn off the system within the time limit to avoid an alarm condition.
- Error: Indicates an invalid keypad entry.
- OK: Indicates a valid keypad entry.
- Watch: Indicates that a watch point is open or faulted. The tone continues until the watch point is closed.

Certifications and Approvals

Keypad Model	Certifications and Approvals
All Models	UL1610 and UL1635, Central Station Alarm Units UL609, Local Alarm Units UL365, Police Station Alarm Units UL1076, Proprietary Alarm Units UL1023, Household Burglar Alarm System Units UL985, Control Units and Accessories-Household System Type
D625 and D625W	ANSI/SIA CP-01-2000, SIA False Alarm Reduction CSFM (:215)

Installation/Configuration Notes

Compatibility Information

Control Panels	D6412 and D4412
----------------	-----------------

Mounting Considerations

- Do not mount any of the D625 Series Keypad models in a location exposed to direct sunlight. Direct sunlight can interfere with screen visibility and damage internal components.
- Do not mount any of the D625 Series Keypad models in locations with temperatures that drop below or exceed the operating temperature range.

Power Supplies

A compatible control panel supplies the power and data requirements to a D625 Series Keypad model through a four-wire connection.

Wiring Considerations

Recommended wiring length is 69 m (225 ft) with 0.8 mm (22 AWG), or 183 m (600 ft) with 1.2 mm (18 AWG). Each D625 Series Keypad model includes a wiring assembly of four color-coded flying leads and one female four-pin connector.

Technical Specifications

Environmental Considerations

Relative Humidity:	5% to 85% at +30°C (+86°F), non-condensing
Temperature (Operating):	0°C to +50°C (+32°F to +122°F)

Keypad

Dimensions for D625 and D625W:	11.7 cm x 21 cm x 2 cm (4.6 in. x 8.2 in. x 0.8 in.)
Dimensions for D625B:	12.6 cm x 20 cm x 3.2 cm (5 in. x 8 in. x 1.3 in.)
Weight for All Models:	439 g (15.5 oz)
Material for All Models:	CHI MEI POLYLAC® PA-757 ABS with UV Stabilizer UL94-HB Fire Rated
Connections:	4-wire flying lead for data and power
Display Window:	2-line, 16-character vacuum fluorescent display with adjustable backlight
Indicators:	Illuminated keys Warning and indicating tones LEDs for Status and On

Power Requirements

Voltage (Operating):	12 VDC nominal, supplied from control panel auxiliary power supply
Current:	Maximum 270 mA Normal 270 mA Standby 270 mA

Trademarks

POLYLAC® is a registered trademark of CHI MEI Industrial Corporation, LTD.
Plexiglas® is a registered trademark of Arkema.

Ordering Information

D625 VFD Keypad Off-white classic case.	D625
D625W VFD Keypad White classic case.	D625W
D625B VFD Keypad White and gray modern case.	D625B

Hardware Accessories

D54B Brass Flush Mount Kit Back box and polished brass faceplate.	D54B
D54C Stainless Steel Flush Mount Kit Back box and stainless steel faceplate.	D54C
D55 Keypad Desk Stand Portable desk stand in smoke colored Plexiglas®.	D55
D56 Surface Mount Conduit Box White surface mount box.	D56
D56R Red Surface Mount Conduit Box Red surface mount box.	D56R

Americas:

Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 27 83955
Fax: +31 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by