

C801 & C802 CELLULAR TELEPHONE INTERFACE

PROGRAM RECORD SHEET

Name (Title): _____

Address: _____

Contact Phone #: _____

Central Station Receiver Phone #: _____

S1 DIPSWITCH SETTINGS				
	Description	Default	Entry	
P1	Cellular Only Mode	OFF		
P2	Delete First Digit	OFF		
P3	No Cellular Service Delay (ON=60 sec., OFF=20 sec.)	ON		
P4	Cellular Service System (ON=Sys.B, OFF=Sys.A)	ON		
P5-	Automatic Self Test Interval (AST)	OFF		
P6-	(No AST=OFF/OFF, Daily=ON/OFF, Weekly=OFF/ON, Monthly=ON/ON)	OFF		
P7	AST Delay 12 Hours	OFF		
P8	Signal Strength/Programming Mode	OFF		
TRANSCIVER NAM PROGRAMMING				
	Prompt	Description	Default	Entry
	01	System Identification Number (SID)	00000	
	02	Cellular Area Code	11	
	03	Cellular Phone Number	111-0111	
	04	Station Class Mark (SCM)	08	08
	05	Access Overload Class (AOC)	15	15
	06	Group ID Mark (GIM)	00	
	07	Security Code	000000	000000
	08	Unlock Code	123	123
	09	Initial Paging Channel (IPC)	0334	
	10	Fixed Options	011100	011100
	11	More Fixed Options	1101	1101
MEMORY RECALL PROGRAMMING				
		Description	Default	Entry
	Location 10	Tone, - 6 sec.	BLANK	
	Location 11	Pulse, - 6 sec.	BLANK	
	Location 12	Tone, • 6 & - 12 sec.	BLANK	
	Location 13	Pulse, • 6 & - 12 sec.	BLANK	
	Location 14	Tone or Pulse, • 12 sec.	BLANK	
	Location 15	Operational Mode	34 (C801)	
			11 (C802)	