



## RF3332 Series Key Fobs



- ▶ Uniquely coded arm and disarm buttons (RF3332 and RF3332E)
- ▶ Panic alarm
- ▶ LED indicator

The RF3332 Series Key Fobs includes the following key fob models:

Model	Frequency	Function
RF3332	304.00 MHz	Arm and /disarm Panic alarm
RF3332E	433.42 MHz	Arm and disarm Panic alarm

All models are wireless and have two buttons. The RF3332 and RF3332E can arm and disarm the security system or send a panic alarm.

### Functions

#### Panic Alarm

Each model can send a panic code to your monitoring company if your security system is programmed to do so. Press both buttons on the RF3332 or RF3332E models simultaneously for two seconds to send a panic alarm.

#### LED Indicator

The LED flashes to indicate a signal was sent to your security system.

### Certifications and Approvals

#### RF3332

Listings and Approvals: Industry Canada (12491021155)

Complies with: FCC (ESV-0407-2)

#### RF3332E

Listings and Approvals: CE

### Installation/Configuration Notes

#### Compatibility Information

Model	Receivers	Control Panels
RF3332	RF3212	Solution Ultima 844, 862, and 880, CC488
	RF3213	VR-8
	RF3222	DS7400Xiv4
	RF3224	DS7240, DS7220, D6412, and D4412
RF3332E	RF3212E	Solution Ultima 844, 862, and 880, CC488
	RF3213E	VR-8
	RF3222E	DS7400Xiv4
	RF3227E	DS7240, DS7220, D6412, and D4412

Model	Receivers	Control Panels
	RF3228E	Marise
	RF3249E	DA (Abacus)

### Recommended Batteries

The following battery types are recommended for correct operation of your key fob: Duracell® DL2025, Eveready® CR2025, or Panasonic® CR2025.

## Technical Specifications

### Environmental Considerations

Relative Humidity:	0% to 95% (non-condensing)
Temperature (operating)::	-29°C to +65°C (-20°F to +150°F) <i>For UL listed requirements, the temperature range is 0°C to +49°C (+32°F to +120°F)</i>

### Mechanical Properties

Dimensions: 3.8 cm x 6.3 cm x 1.3 cm (1.5 in. x 2.5 in. x 0.5 in.)

### Power Requirements

Batteries:	Two 3 VDC lithium batteries
Battery Life:	Approximately 5 years under normal operating conditions with recommended battery types

### Transmission Characteristics

Maximum RF Power: Less than 10 mW

### Frequency

RF3332E:	433.42 MHz
RF3332:	304.00 MHz

### Trademarks

Duracell® is a registered trademark of the Gillette Company, USA, in the United States and/or other countries.

Eveready® is a registered trademark of Eveready Battery Company, Inc.

Panasonic® is a registered trademark of Matsushita Electric Industrial Co., Ltd.

## Ordering Information

RF3332 Two-Button Wireless Key Fob (304 MHz)	RF3332
RF3332E Two-Button Wireless Key Fob (433.42 MHz)	RF3332E

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

### Represented by