

# GE Security

NetworX's **NX-1700E** cost-effective proximity card reader/door control module expands the capability of NetworX control panels without the need for any additional interface devices. Connect up to 15 readers to any NX series control panel data bus, as far as 2,500 feet away.

The NX-1700E Smart Reader uses proprietary proximity cards or keyfobs. Cards can arm or disarm the system and open the controlled door. Cards follow user authority levels, eliminating the need to create access groups. The system logs arm and disarm activity by user.

The Smart Reader also includes a low-current trigger output for operating a door strike/magnetic lock, one egress input (for a request-to-exit button), a programmable optical tamper switch, and LEDs that can be programmed to follow the output or armed/ready status of the system. The built-in sounder can also be programmed to follow NX keypad sounds.

The NX-1700E can be programmed to control access in one or all partitions with a single card swipe. Cards and keyfobs are easy to enroll, either individually or in batches. Users can also add and delete cards from the system using DL900 software.

Installation of the NX-1700E reader is fast and easy, with no DIP switch addressing required.

## Features

- Uses proximity cards or keyfobs
- Connect up to 15 readers to any NX series control panel
- Locate readers up to 2,500 feet from the control panel
- Control access in one or all partitions
- Enroll cards and keyfobs individually or in batches
- NX-1705E smart cards and NX-1706E smartfobs available
- Add and delete users with DL900 software
- One low-current trigger output for door strike/magnetic lock
- Now includes scheduling function

## NetworX™ NX-1700E Smart Reader





Americas  
503-885-5700  
888-GE-SECURITY  
(437-3287)  
faxback 800-483-2495  
info@gesecurity.com  
www.gesecurity.com

---

Asia  
tel 852-2907-8108  
fax 852-2142-5063

Australia  
tel 61-3-9259-4700  
fax 61-3-9259-4799

Europe  
tel 32-2-725-11-20  
fax 32-2-721-86-13

Latin America  
tel 305-593-4301  
fax 305-267-4300

## Specifications

### Electrical

- Voltage: 12 VDC (supplied by control panel)
- Current: 40 mA standby; 110 mA maximum

### Features

- Panel compatibility: NetworkX NX-4, NX-6, NX-8, and NX-320E control panels
- Up to 15 readers per control panel
- Up to 2,500 ft. (762 m) of wire between reader and panel

### Environmental

- Operating temperature: 32 to 120°F (0 to 49°C)
- Storage temperature: -30 to 140°F (-34 to 60°C)
- Maximum humidity: 15 to 90% noncondensing

### Physical

- Dimensions (LxWxD): 4.5 x 1.5 x 1.0 in. (114 x 38 x 25 mm) with 6-ft. (1.8 m) cable
- Installation: Surface mount
- Color: White

### Regulatory

- FCC Part 15

### Ordering information

NX-1700E NetworX Smart Reader  
NX-1705E Smart Card  
NX-1706E Smart Fob