

- **Expandable To 12 Hardwire /16 Wireless Zones**
- **Maximum of 8 Keypads With Up To 8 Per Partition**
- **Up To 2 True Partitions With Separate Account Codes, Entry/Exit Delays, And Feature Selections For Each Partition**
- **Forty User Codes**
- **185-Event History Log that Provides Date, Time, Event And User Number**
- **ITI Wireless Technology With Up To 16 Supervised Zones**
- **Hardwire Expansion Up To 16 Zones.**
- **Supports SIA And Contact ID Communication Formats**



NX-1316E KEYPAD

NX-116E KEYPAD

## The Power of One — from CADDX

### Overview

The NX-6 is a full-featured, mid-sized security system that uses advanced technology for burglary, fire and environmental detection. The NX-6 is a flexible security system that is easy to install and simple to use. With two partitions and up to sixteen zones, the NX-6 can handle most medium size residential and commercial security needs.

### High Standards

The panel comes standard with six hardwire zone inputs. Four programmable outputs can be set up to activate external devices during an alarm or other system event. The Modular design allows for complete integration of multiple systems within one enclosure. Adding more zones or expanding capability is fast and easy.

### Easy Expansion

Expand the NX-6 capabilities by adding up to three optional Expander Modules. Modular design allows NetworX modules to slide into the enclosure easily for quick installations.

The NX-320E Smart Power Supply and Bus Extender, the NX-508E Output Module and the NX-534E Two-Way Voice Module are just a few of the flexible options for the NX-6.

Expand the system even further with a phone interface/voice module for on-site and off-site system control using touchtone phones.

### Effortless Programming

Conduct quick and easy on-site programming with alphanumeric keypads and a menu driven text interface. Off-site programming is also available with the DL-900 software for Windows.

CADDX NX-6



# CADDX® NX-6 Control Panel

## AVAILABLE KEYPAD STYLES



LED



FIXED DISPLAY WITH REMOVABLE DOOR



LED WITH REMOVABLE DOOR



LCD WITH REMOVABLE DOOR

## SPECIFICATIONS

Operating power	16.5VAC 40VA
Auxiliary power	
w/40VA or 50VA transformer	1 Amps
w/NX-320E power supply	3 Amps*
Loop resistance	
For standard loop	300 Ohms Maximum
For 2-wire smokes	30 Ohms Maximum
Built-in siren driver	2 Tone (Temporal & Yelp)
Alarm current available (if above driver is not used)	2.5 Amps
Loop response	500ms
Operating temperature	32F to 120 °F (0 to 49 °C)
LCD keypad dimensions	6.4"W 4.0"H 1.1" D
LED keypad dimensions	6.4"W 5.3"H 1.0" D
Keypad material	White / ABS
Enclosure dimensions	11.25"W 11.25"H 3.5" D
Enclosure color	Off White
Shipping weight	9 lbs

\*When using the NX-320E (w/50VA transformer) rated at 2 Amps and NX-8 (w/40VA or 50VA transformer) rated at 1 Amp, the combined available power is 3 Amps.

## ORDERING INFORMATION

MODEL NO.	DESCRIPTION
NX-6	6-zone control only. Keypad and transformer sold separately.
NX-6-KIT	6-zone control with NX-108E keypad and transformer.
NX-108E	8-zone LED keypad.
NX-1316E	16-zone LED keypad with removable door.
NX-1448E	48-zone fixed display LCD keypad.
NX-148E	48-zone custom display LCD keypad with removable door.
NX-408E/416E	8, 16-zone wireless expander receivers.

Contact your local distributor or Interlogix representative for a complete list of Caddx parts and accessories.



1420 NORTH MAIN GLADEWATER, TX 75647

SALES USA & CANADA: 800-547-2556

TECHNICAL SERVICE: 800-727-2339

www.caddx.com

© 2001 Interlogix, Inc.

Interlogix reserves the right to change specifications without notice.

Caddx® is a registered trademark of Interlogix, Inc.