

GE Security

New features

- Flash memory microprocessor
- Expanded event log
- Early open/late close reporting

Standard features

- Expandable to 48 fully programmable hardwire and/or wireless zones
- Maximum of 24 keypads with up to 8 per partition
- 8 true partitions with separate account codes, entry/exit delays, and feature selections for each partition
- Wireless technology with up to 48 supervised zones
- Supports up to 99 users
- Hardwire expansion up to 48 zones
- Supports SIA and contact ID communication formats
- 512-event history log that provides date, time, event and user number

Overview

The NetworX NX-8 is a full-featured security system that uses advanced technology for burglary, fire and environmental detection. The NX-8 is a flexible security system that is both easy to install and simple to use. With eight partitions and up to 48 zones, the NX-8 can handle big or small residential and commercial security needs.

Outstanding features

The NX-8 panel comes standard with eight hardwire zone inputs. Four programmable outputs can be set up to activate external devices during an alarm or other system event. The modular design allows for complete integration of multiple systems within one enclosure. Adding more zones or expanding capability is fast and easy.

Convenient and flexible

Conduct quick and easy on-site programming with alphanumeric keypads and a menu-driven text interface. Off-site programming is also available with the DL-900 software for Windows.

NetworX Control Panel NX-8



NetworX Control Panel NX-8

Specifications

- Operating Power – 16.5V AC 40VA
- Auxiliary w/40VA or 50VA transformer – 1 Amp
- Auxiliary w/NX-320E power supply – 3 Amps*

Loop resistance

- For standard loop – 300 Ω Maximum
- For 2-wire smokes – 30 Ω Maximum

Operating temperature

- 32 to 120°F

Dimensions

- 6.40 inches wide
- 4.0 inches high
- 1.10 inches deep

Shipping weight

- 9 pounds

** When using the NX-320E (w/50VA transformer) rated at 2 Amps and NX-8 (w/40VA or 50VA transformer) rated at 1 Amp, the combined available power is 3 Amps.*

Available Keypad Styles



LED



LCD with
Removable Door



Fixed Display with
Removable Door



LED with
Removable Door

NetworX Technical Support: 800-727-2339

12345 SW Leveton Drive
Tualatin, OR 97062
Phone: 503-692-4052
USA & Canada: 800-547-2556
Technical Service: 800-727-2339
Faxback: 800-483-2495

1275 Red Fox Road
Arden Hills, MN 55112
Phone: 651-777-2690
USA & Canada: 800-777-5484
Technical Service: 800-777-2624

www.gesecurity.com