



www.GE-Interlogix.com

## NetworX NX-8-CF

Integrated Commercial Intrusion/Fire System

### Grow Your Business with the Platform You Know

Now you can get a UL 864 listed commercial fire solution with the programming ease and flexibility of NetworX. The NX-8-CF is a 12V integrated burglary/fire product for commercial applications. It's the simple way to expand into commercial fire without the cost and frustration of learning a new platform.

### Powerful Performance

The NetworX NX-8-CF provides 48 zones of protection for fire and intrusion. It also supports an array of accessories and modules, including cellular backup and door access control. It's ideal for applications where integrated systems provide the most comprehensive, cost-effective solution.

### Programmed For Convenience

Since the NX-8-CF is based on the proven NetworX platform, you already know how to program and install the panel quickly and easily. It comes with eight hardwire zone inputs and four programmable outputs that can be set up to activate external devices during an alarm event. The dedicated programmable notification appliance circuit outputs a temporal code and is individually silenceable. To meet the UL 864 requirement for commercial fire, the NX-8-CF has a NX-870E module for dual phone line supervision.

GE Interlogix security and life safety products are designed to work together and provide the most comprehensive solution for security professionals.



### Standard Features

- Supports up to 20 two-wire smoke detectors. Four-wire smoke detectors can be used with hardwired initiating devices up to 48 zones
- Supports one NAC for horns and strobes
- Supports hardwire or wireless intrusion detection devices for maximum flexibility and quick installation
- The NX-1700E module provides access control for up to fifteen door.
- The NX-591E\* offers secure alarm transmission in case of line cut or other telephone service interruption. Intrusion only
- The NX-216E allows expansion with any mix of fire and intrusion up to 48 zones
- NX-320E power supply allows additional power to be added in 2-Amp increments

\* Not UL 864 listed for the NX-8-CF

# NetworX NX-8-CF

Integrated Commercial Intrusion/Fire System

## Specifications

**Operating Power** 16.5V AC 50VA transformer

**Auxiliary Power**  
**w/ 50VA transformer** 12V AC 1 Amp  
**w/NX-320 power supply** 12V AC 2 Amps

**Loop Resistance**  
**Standard Loop** 300 Ohms Max.  
**2-wire smokes** 30 Ohms Max.

**Loop Response** Selectable 50ms or 500ms

**Operating Temperature** 32° to 120°F

### NX-148-CF LCD keyboard

**Current draw** 110mA max.  
**w/o sounder** 75 mA  
**Dimensions** 6.4 W x 5.3 H x 1.0" D

**Enclosure Dimensions** 15.5 W x 18.5 H x 4.5" D

**Shipping Weight** 20lbs.

## UL Listings

**Residential and Commercial UL Burglary ratings**  
**UL 609 Commercial**  
**UL 1023 Residential Burglary**  
**UL 1610 Grade B & C Central Station Burglar Alarm**  
**UL 1637 Home Health Care Signaling**

**NX-8-CF Fire Panel had UL 864 rating for commercial fire**  
**Type L**  
**Type RS**  
**Type CS**



NetworX Technical Support: 800-727-2339

## Ordering Information

| Model       | Description                                                           |
|-------------|-----------------------------------------------------------------------|
| NX-8-CF-Kit | Includes NX-8-CF with NX-870E, (2) NX-148E-CF keypads and transformer |
| NX-8-CF     | Control panel plus NX-870E in red commercial fire/burg enclosure      |
| NX-148E-CF  | Alphanumeric LCD red keypads                                          |
| NX-870E     | Dual phone line fire supervision module                               |
| Transformer | 16.5V, 50VA                                                           |



**GE Interlogix**

www.GE-Interlogix.com

12345 SW Leveton Drive  
Tualatin, OR 97062  
Phone: 503-692-4052  
USA & Canada: 800-547-2556  
Technical Service: 800-648-7424  
Faxback: 800-483-2495

2266 Second Street North  
North St. Paul, MN 55109  
Phone: 651-777-2690  
USA & Canada: 800-777-5484  
Technical Service: 800-777-2624