

- Expandable To 192 Fully Programmable Hardwire And/Or Wireless Zones
- 240 User Codes
- 512-Event History Log That Provides Date, Time, Event, Partition And User Number
- Up To 8 True Partitions With Separate Account Codes, Entry/Exit Delays, And Feature Selections For Each Partition
- Maximum Of 32 Keypads With Up To 8 Per Partition
- ITI Wireless Technology With Up To 192 Supervised Zones
- 2-Wire Or 4-Wire Smoke Detector Compatibility
- Fire Alarm Verification For Greater False Alarm Immunity
- Dynamic Battery Test
- Standard RS232 On-Board Interface
- Open Architecture Design For Future Flexibility



The Power of One — from CADDX

Overview

Our best full-featured commercial and residential security system, the NX-8E uses advanced technology for burglary, fire and environmental detection. The NX-8E is a flexible security system that is easy to install and simple to use. With eight partitions and up to 192 zones, the NX-8E can handle your most demanding commercial and residential security needs.

High Standards

The panel comes standard with eight hardwire zone inputs and two relays. Four programmable outputs can be set up to activate external devices during an alarm or other system event. The modular design allows for complete integration of multiple systems within one enclosure. Adding more zones or expanding capability is fast and easy.

Easy Expansion

Expand the NX-8E with up to 32 expander modules. Modular design allows NetworX modules to slide into the enclosure easily for quick installations. The NX-320E Smart Power Supply and Bus Extender, the NX-508E Output Module and the NX-534E Two-Way Voice Module are just a few of the flexible options for the NX-8E.

The NX-540E Phone Interface/Voice Module allows on-site and off-site system control using true touch-tone phones. For advanced automation, the NX-8E interfaces with a variety of Caddx automation partners.

Effortless Programming

Conduct quick and easy on-site programming with alphanumeric keypads and a menu driven text interface. Off-site programming is also available with the DL-900 software for Windows.

CADDX NX-8E



CADDX® NX-8E Control Panel

AVAILABLE KEYPAD STYLES



LED



FIXED DISPLAY WITH REMOVABLE DOOR



LED WITH REMOVABLE DOOR



LCD WITH REMOVABLE DOOR

SPECIFICATIONS

| | |
|---|---------------------------|
| Operating power | 16VAC 40VA |
| Auxiliary power | |
| w/40VA or 50VA transformer | 2 Amps |
| w/NX-320E power supply | 4 Amps |
| Loop resistance | |
| For standard loop | 300 Ohms Maximum |
| For 2-wire smokes | 30 Ohms Maximum |
| Built-in siren driver | 2 Tone (Steady & Yelp) |
| Alarm current available (if above driver is not used) | 2.5 Amps |
| Loop response | 500ms |
| Operating temperature | 32 to 120 °F (0 to 49 °C) |
| LCD keypad dimensions | 6.4"W 4.0"H 1.1" D |
| LED keypad dimensions | 6.4"W 5.3"H 1.0" D |
| Keypad material | White / ABS |
| Enclosure dimensions | 11.25"W 11.25"H 3.5" D |
| Enclosure color | Off White |
| Shipping weight | 9 lbs |

Approvals UL 609, UL 635, UL 985, UL 1023, UL 1610, UL 1635, UL 1637

The UL 609 rating only applies when using the NX-003C UL commercial enclosure.

When using the NX-320E (w/50VA transformer) rated at 2 Amps and NX-8E (w/40VA or 50VA transformer) rated at 2 Amp, the combined available power is 4 Amps.

ORDERING INFORMATION

| MODEL NO. | DESCRIPTION |
|-------------------|--|
| NX-8E | 8-zone control only. Keypad and transformer sold separately. |
| NX-848E-KIT | 8-zone control with NX-148E LCD keypad and transformer. |
| NX-108E | 8-zone LED keypad. |
| NX-1316E | 16-zone LED keypad with removable door. |
| NX-1448E | 48-zone fixed display LCD keypad. |
| NX-148E | 48-zone custom display LCD keypad with removable door. |
| NX-216E | 16-zone hardwire expander module. |
| NX-408E/416E/448E | 8, 16, 48-zone wireless expander receivers. |
| NX-003C | UL commercial enclosure for NX-8E. |
| NX-005C | Tamper switch and bracket for NX-003C. |

Contact your local distributor or Interlogix representative for a complete list of Caddx parts and accessories.



1420 NORTH MAIN GLADEWATER, TX 75647

SALES USA & CANADA: 800-547-2556

TECHNICAL SERVICE: 800-727-2339

www.caddx.com

© 2001 Interlogix, Inc.

Interlogix reserves the right to change specifications without notice.

Caddx® is a registered trademark of Interlogix, Inc.