



Micro Multipurpose Panic Button

Overview

The Panic Button is a water-resistant wireless device used for activating police, medical, or auxiliary alarms throughout the premises. When the panic button is pressed, the LED mounted under the front cover will blink and an alarm signal is transmitted.

The status of the battery is sent in every transmission. The battery is field replaceable.

The button has five adapters which easily fit onto the panic button. Using these adapters the panic button can be mounted on the wall, worn as a belt clip, as a watch, or as a pendant.

Ordering Information

Main Product Offering

Micro Multipurpose Panic Button

Part Number

60-906-95

Literature

Installation Instructions

Part Number

466-1815



Specifications

Compatibility

- All 319.5 MHz Learn Mode panels

Power Supply

- One 3.0 VDC Duracell (DL2032) lithium battery

Indicators

- One module/panel communications status LED

Frequency

- 319.5 MHz

Transmitting Range

- At least 375 feet open-air range

Temperature

- Operating: 32° to 120° F (0° to 49° C)
- Storage: -30° to 140° F (-34° to 60° C)

Maximum Humidity

- 90% relative humidity, noncondensing

Enclosure

- Water-resistant rating to IPX7 (1 meter for 30 minutes)

Standards/Listings

- FCC Part 15

Dimensions

- Without adapters or wrist band 1.5" x 1.3" x .5" (L x W x D)





GE Interlogix

www.GE-InterlogixSecurity.com

*12345 SW Leveton Drive
Tualatin, OR 97062
Phone: 503-692-4052
USA & Canada: 800-547-2556
Technical Service: 800-648-7424
Faxback: 800-483-2495*

*2266 Second Street North
North Saint Paul, MN 55109
Phone: 651-777-2690
USA & Canada: 800-777-5484
Technical Service: 800-777-2624*