



GTS 50

Touchscreen Interface for Your Security System

Overview

The wall-mounted GTS 50 touchpad is a touchscreen interface for a security system. The touchscreen technology enables the user to perform system commands by touching icons on the touchpad screen (touchscreen). Changes made on the system automatically show on the touchscreen, enabling the user to maintain and reprogram the system.

The GTS 50 is compatible with Concord™ panels version 3.0 and later.

Applications

The GTS 50 is designed with everything necessary to operate and program the system.

- Arm the system (doors, windows, and motion sensors).
- Arm the system with No Entry Delay.
- Disarm the system.
- Activate a panic alarm to call the central monitoring station in a non-medical emergency.
- Check system status.
- Turn system controlled lights on or off (all or individual).

Standard Features

- **Separate screens for installer and user programming**
- **Mounts recessed inside existing walls**
- **Separate instruction manuals for installers and users**



Specifications

Compatibility:

- Concord panels version 3.0 and later

Dimensions

- 5.875 x 4.5 x 2.3 in. (W x H x D) 15 x 11.5 x 5.8 cm

Operating Temperature

- 32° F to 120° F (0° C to 49° C)

Power Requirements

- 12 VDC nominal, 300 mA

Ordering Information

Main Product Offering

GTS 50

Part Number

600-1013

Literature

GTS 50 Installation Instructions

GTS 50 User Guide

Part Number

466-2192

466-2191





GE Security

*1275 Red Fox Road
Arden Hills, MN 55112
USA & Canada: 800-777-5484
Technical Support: 800-777-2624*