

▪ **FONSAFE SYSTEM FEATURES**

- **Monitors up to 32 wireless sensors**
- **Patented Learn Mode technology**
- **Light control**
- **Appliance control**
- **Listen-in/Talk back**
- **Voice menu**
- **On/Off-premises phone control**
- **24 hour backup battery (if fully charged)**
- **Single button arming**
- **Two user passwords**

■ FONS SAFE SPECIFICATIONS

- Dimensions: 8.7" X 10.5" X 3"
- Weight: 5 lbs. 11 oz.
- Installation Options: table top or wall mount
- Main Operating Voltage: 110 VAC, 60 Hz (200 mA fuse)
- Backup Battery: 6 VDC, 3.2 Ah, rechargeable, sealed lead acid battery. Provides up to 24 hours with fully charged battery.
- MCU Memory: If AC power is lost, MCU memory may be saved for up to 14 days.
- Zones: 32
- Radio Frequency: 319.508 MHz
- Nominal Range: 500' free air (152 m)
- Supervision: MCU receives supervisory transmission from each sensor every 64 minutes; sensors supervise their own battery voltage and notify the MCU if their battery voltage is low.
- Dialing Method: pulse or dual tone multi-frequency (DTMF)
- Standards/Approvals:
 - UL 1023 Standard for household burglar alarm system units
 - FCC Part 15 and FCC Part 68
 - California Fire Marshall approval pending
- Operating Temperature: 40-100°F
- Maximum Relative Humidity: 70% non-condensing