



Simon Control Panel

ITI Part No.: 60-776-95R
60-776-01-95R

*Affordable,
Reliable Security
Featuring ITI
Learn Mode
Technology*

Overview

The Simon™ Security System delivers a low-cost security panel designed to provide years of reliable burglary detection, fire protection, and home automation control. With a built-in touchpad and a status speaker that provides voice messages for feedback, Simon is well-suited for houses, apartments, and condominiums.

Outstanding Features

Simon is quick and easy to install thanks to patented ITI Learn Mode™ technology that eliminates cumbersome sensor programming. The wall-mounted wireless Simon TouchTalk™ 2-Way RF Touchpad combines a conventional ITI Learn Mode touchpad with an RF receiver, speech chip, and voice amplification circuit. Using remote phone control, you can arm and disarm the system, control system lights, check system status, activate no entry delay, or activate latchkey. With latchkey capabilities, you can program the panel to dial a pager phone number in the event that the system has not been disarmed at a scheduled time.

Standard Features

- 24 individual sensor zones with options for up to 2 hardwire zones
- 319.5 MHz SAW receiver will support all ITI Crystal and SAW sensor line devices
- 5 user-programmable access codes
- Chime feature for monitoring door and window activity
- Indoor and outdoor motion sensors
- Central station and numeric pager reporting
- Event buffer with a time stamp
- Panel voice and panel beeps can be disabled
- Settings and new accounts can be programmed from off-site using ITI ToolBox
- SAW sensors with user-replaceable alkaline batteries
- 4-button keychain touchpad capability

Expansion Options

- Up to eight individual light or appliance control units can be installed and controlled from touchpads (requires X-10® Lamp Modules or appliance modules)
- An X-10 Universal module is necessary for garage door opener control

Touchpad Options

- HiTech Handheld Touchpad
- 2-button and 4-button SAW and Crystal Keychain Touchpads
- TouchTalk 2-Way RF Talking touchpad
- Wall-mount panel
- Optional table-mounting base

Easy Expansion

With built-in capabilities for easy system expansion, Simon is enhanced through the addition of optional modules that perform such functions as controlling lighting and opening a garage door.

Enhanced Monitoring

Simon can be a monitored security system that sends messages to a central monitoring station or a numeric pager carried by a designated user. One remote Interrogator® 200 module may be added to the system to provide additional security and emergency contact with the central monitoring station.

Effortless Programming

Programming is a simple procedure that is done on-site with the built-in touchpad or off-site with ITI ToolBox® downloader software (versions 4.3 and later).



Simon Family Literature

Product Catalog

ITI Part No.: 466-1242-SM

Dealer Price List

ITI Part No.: 466-1289-01-SM

Main Product Offering

Simon Panels

ITI Part No.: 60-776-95R

60-776-01-95R

Specifications

Power Supply

Required Transformer

Class II, 9 VAC, 60 Hz (22-091-ITI)

Backup Batteries/Backup Time

9 VDC, 1.2 Ah Ultralife Lithium (34-037) - 24 Hours (fully charged)

7.2 VDC, 1 Ah Nickel Metal Hydride Rechargeable (32-052) - 30 hours - UL approved

7.2 VDC, 650mAH Nickel Metal Hydride Rechargeable (34-051) - 18 hours -not UL approved

15 seconds under load every four (4) hours

Non-replaceable transformer fuse

Battery Test

Fuse

Radio Receiver

Type

SAW-Controlled Superheterodyne

Frequency

319.5 MHz

Bandwidth

350 kHz

Sensitivity

-112 dBm nominal

Nominal Range

500 ft. (150 m) open-air receiving range

Telephone/Modem

Dialing

DTMF or pulse

Modem

Modified Bell 103 (110 or 300 bps)

Telephone Interface

Line seizure relay

Inputs/Outputs

Total Input Zones

24

Auxiliary Power

Regulated, fused 7-12 VDC output 250 mA (maximum)

Siren Outputs

Hardwire Interior Siren (HIS) output and Hardwire Exterior Siren (HES) output (7-12 V)

Microprocessor

Processor Type

Mitsubishi M38024M6-SP

Processor Clock

7.68 MHz

System ROM

24 kilobytes

System RAM

640 bytes

Memory Retention

Unlimited duration (512 bytes EEPROM)

Digitized Voice

Digitization Type

Linear Predictive Coding (LPC)

Playback Rate

16,000 bits/second (varied by word)

Vocabulary Size

212 words (approximately 90 seconds)

Environmental

Operating Temperature

32° (0°C) to 122°F(50°C)

Maximum Humidity

85% relative humidity, noncondensing

Standards

FCC Part 15, FCC Part 168

UL Listings 985, 1023

Physical Description

Color

Belgian Gray

Dimensions

9.5" x 7.5" x 1.5" (L x W x H)

Weight

1.6 lbs.

Installation

Wall and table mounting

Chassis Material

ABS

ITI Document Number: 466-1598 Rev. B

(Specification sheets available in quantities of fifty)

Copyright © 1999, Interactive Technologies, Inc.

ITI, ITI ToolBox, and Simon are registered trademarks of Interactive Technologies. Specifications are subject to change without notice.

Phone: 1-800-777-5485 FAX: 1-651-779-4890

Interactive Technologies, Inc. • 2266 Second Street North, North Saint Paul, MN 55109 • www.itii.com

Security
Automation
Fire Protection
Access Control

