



Dialog 2-Way RF Touchpad

Reliable and Convenient Touchpad for Basic System Operation

Overview

The wall-mounted wireless Dialog 2-Way RF Touchpad combines a conventional Learn Mode touchpad with an RF receiver, speech chip, and voice amplification circuit for your Simon® 3 security system. The touchpad allows the user a convenient option for basic Simon 3 system operation within the home. It allows the user to enter commands and hear feedback from the panel

Specification

Voice Feedback is heard only at the touchpad that is in use. If the touchpad is talking, the panel is silent. When the panel is talking, the touchpad is silent. The touchpad is not a siren and will not make any alarm sounds or status beeps. This feature extends battery life to the touchpad and gives feedback only to the user who needs it, which assures the touchpad is silent when not in use, making it ideal for bedrooms.

Sensors: The touchpad is programmed into the Simon 3 panel as a non-supervised sensor using sensor group 01, 03, 06 or 07. Each learned touchpad uses one of the available sensor numbers (24 total sensors/zones can be used with the Simon 3 panel).

Mounting Location: The touchpad is mounted on the wall. It might not work properly if mounted too close to the Simon 3 panel. It should be mounted within 100 feet of the control panel.

Applications

- Auxiliary control in homes where there are multiple entry and exit points
- Auxiliary control in homes where there are multiple levels
- When more than one system control point is desired

Standard Features

- Arming the system (doors, windows and motion sensors)
- Arming the system with No Entry Delay
- Disarming the system
- Activating a panic alarm that calls the central monitoring station with a non-medical emergency
- Checking system status
- Turning system controlled lights on and off (all or individual)
- Enables the user to hear voice feedback that is heard at the Simon 3 Control Panel



Specifications

Compatibility

- Simon 3 version 3.3 or later

Dimensions

- 3.6 x 1.2 x 5.4 in.(W x D x H) 37 x 45.8 x 7.8 cm

Operating Temperature

- 32°F to 120°F (0°C to 49°C)

Power Requirements

- 3 AAA Alkaline batteries

Ordering Information

Main Product Offering

Dialog 2-Way RF Touchpad

Part Number


60-924-3

Literature

Dialog 2-Way RF Touchpad Installation Instructions

Part Number

466-1962





GE Interlogix

www.GE-InterlogixSecurity.com

12345 SW Leveton Drive
Tualatin, OR 97062
Phone: 503-692-4052
USA & Canada: 800-547-2556
Technical Service: 800-648-7424
Faxback: 800-483-2495

2266 Second Street North
North Saint Paul MN 55109
Phone: 651-777-2690
USA & Canada: 800-777-5484
Technical Service: 800-777-2624