

Two-way, Fully Wireless Outdoor Siren

For many home owners, the advantages of an outdoor wireless siren are outweighed by complicated installation and wiring costs. The MCS-730 two-way, fully wireless outdoor siren overcomes these challenges through easy, cabling-free installation and optional extended time between battery changes, for long-lasting operability. In addition, two-way and fully supervised communication with the control panel assures highly reliable operation.

This affordable siren's sleek design ensures it is clearly visible, alerting and deterring potential intruders, while maintaining the clean look of any building. In the event of an alarm, the siren sounds loudly and the strobe light is activated, ensuring the alarm is noticed.

- Sleek design and high power strobe light provide visual deterrence to potential intruders, while maintaining a clean building facade
- Large free screen-print area
- Choice of red, blue, orange or white strobe light lens
- Easy, cabling-free installation
- Robust design and weatherproof housing
- Two diversity antennas for optimal wireless performance



# MCS-730 Two-way, Fully Wireless Outdoor Siren

## **Key Features & Benefits**

#### >> Versatile solution fits varied design needs

- Contemporary, sleek design with choice of red, blue, orange or white strobe light lens
- Large free screen-print area available for company logo and information

#### Highly reliable and cost-effective

- Two-way fully-supervised communication with the control panel
- Two diversity antennas for optimal wireless performance
- ▶ Audible and visual notifications of intrusions, fires, low battery voltage, and communication disruptions
- lssues a different alarm sound for burglaries and fires
- Audial arming and disarming confirmation
- 110dB piezo siren
- ▶ High-power strobe light
- Double tamper protection (wall and cover)
- ▶ IP55 rating, with increased protection from dust and moisture
- Robust design for protection against harsh external conditions - including UV radiation from direct sunlight

### **Easy to install and maintain**

- Fully wireless, battery-operated, with no power supply required
- Convenient and rapid no-mess installation
- Option of two batteries to enable longer life\*
- Self-test for checking the siren and strobe lights prior to installation
- ► Compatible with selected versions of PowerMax™Pro, PowerMaxComplete and PowerMaxExpress\*\*

•Head Office (Israel) Tel (+972-3) 645 6789 •Visonic Iberica de Seguridad (Spain) Tel (+34-91) 659 3120

•Visonic Inc. (U.S.A) Tel (+860) 243 0833 •Visonic Deson Limited (Hong Kong) Tel (+852) 2157 7147

•Visonic Limited (U.K.) Tel (+44-870) 730 0800 •Visonic GmbH (Germany) Tel (+49) 211 600 6960

•Visonic Ltd. (Nordic) Tel (+47) 6758 0843 •Visonic Sp. z o.o. (Poland) Tel (+48-22) 639 3436 •Visonic Ltd. (South Africa) Tel (+27) 84 577 8668

#### For more information, visit: www.visonic.com

■ Wisonic and PowerMax are registered trademarks of Visonic Ltd. Other names are the property of their owners. Visonic reserves the right to change information or specifications without notice.
VISONIC LTD. MCS-730 DATA SHEET ENG C-800498 (Rev. 00)
Designed by Linor Ankri



MCS-730

#### **Strobe Windows:**









Specifications

**Power supply:** 3.6v non rechargeable

Lithium battery

**Battery life expectancy:** 3 years (with typical use)\*

Sound output: 110dB@1m

Operating frequency (MHz): 315, 433.92, 868.95
Strobe frequency rate: 1 flash per second
Dimensions (L x W x D): 295 x 186 x 63mm

(11-5/8 x 7-5/16 x 2-1/2in)

Weight (including battery): 970g (34oz)

**Operating temperature:** -25° - 70°C (13° - 158°F)

**Certifications:** EN 50131-1 Grade 2 Class 4,

CFR Part 15, RSS210, IP55,

EN 30131-4

- \* Only one battery included. The second battery to extend life must be purchased separately.
- \*\* Check the control panel's manual for compatibility.

